



# PALRUF®

Corrugated PVC Sheet



## ► Overview

PALRUF is a highly durable corrugated PVC sheet. Its excellent chemical resistance makes it ideal for roofing, siding and cladding in industry, agriculture, construction and DIY. PALRUF is easy to install and maintain, and is available in a wide variety of profiles and colors.

## ► Main Benefits

- Excellent chemical resistance
- Weather and UV resistant
- High fire resistance
- PALRUF® HYG: Active hygiene
- Will not rust or corrode
- Ideal for arched roofs & curved walls
- High impact - Resists breakage
- Easily handled, quickly installed
- Requires minimum maintenance

## ► Applications














- **Industry:** Chemical & pharmaceutical plants, pulp & paper plants, power stations, mining and metal processing facilities
- **Agriculture:** Greenhouses, cow sheds, poultry houses, pigpens, barns and machinery sheds
- **Food Manufacturing**
- **Construction:** Coastal construction, public Buildings, Parks, Sports and recreation Facilities and Pavilions
- **Do-It-Yourself:** Greenhouses, sun houses, skylights, garages (carports), porches, patio enclosures, sundecks/verandas, pool enclosures, awnings, partitions and gazebos (pergolas)



## ► PALRUF® Product Range

Product	Description
AG-TUF®	Liner panel for indoor applications
PALRUF® Opaque	Opaque sheet inherently UV resistant, suitable for all applications
PALRUF® Clear	Clear UV stabilized sheet, ideal for DIY applications
PALRUF® Opal	UV stabilized sheet, reduced light transmission (~35%)
PALRUF® High Impact	With increased impact resistance and durability

## ► Profiles and Standard Dimensions

Type	Profile*	Drawing	Thickness (mm)	Width (mm)	Length (mm)
Mini	207/35		0.8	660, 750, 1040	1.5 - 6.0
Iron/Sinus 76	76/18		0.8 - 1.5	660, 860, 900, 1150	1.5 - 11.6
Greca/Trapeze	76/18		0.8 - 1.3	1045, 1060, 1140, 1145, 1190	1.5 - 11.6
Greca/Trapeze	75/19		0.75 - 1.0	1135	1.5 - 11.6
Greca/Trapeze	70/18		0.8 - 1.5	550, 765, 1090, 1103	1.5 - 11.6
5,6 Waves	177/51		0.8 - 2.0	920, 1100, 1170	1.5 - 6.0
3" Standard	72/20		0.8, 1.0, 1.3	755	1.5 - 11.6
American 4.2"	107/27		1.8 - 4.5	1070	1.5 - 11.6
American 2.6"	67.8/20		2.0	1020	1.5 - 6.0
Big 6"	146/48		1.1, 1.3, 2.0	1086	1.5 - 6.0
Astoria	305/38		2.2	1015	1.5 - 6.0
Industrial 0100	250/40		1.8 - 3.0	1066	1.5 - 6.0
7.2"	183/38		2.0 - 3.0	967, 1150, 1217	1.5 - 11.6

\*Custom designed profiles are available for guaranteed minimum order.

## ► Colors

Opaque	White, Light Grey, Beige, Light Green Light Blue
Transparent	Clear, Bronze
Translucent	White Opal, White Diffuser, Blue

## ► Typical Physical Properties

Property	Method*	Conditions	Units	Value
Density	D-792		g/cm <sup>3</sup>	1.4
Heat deflection temperature (H.D.T)	D-648	Load: 1.82 MP	°C	61 - 67
Service Temperature Range			°C	-20 to +50
Thermal conductivity	C-177		W/m K	0.16
Coefficient of linear thermal expansion	D-696		cm/cm°C	6.3 x 10 <sup>-5</sup>
Impact strength	ISO 6603/1	2 mm sheet	J	45 - 60
Tensile strength at yield	D-638	10 mm/min	MPa	52 - 66
Tensile strength at break	D-638	10 mm/min	MPa	39 - 53
Elongation at yield	D-638	10 mm/min	%	3
Elongation at break	D-638	10 mm/min	%	140 - 160
Tensile modulus of elasticity	D-638	1 mm/min	MPa	2,700
Flexural strength	D-790	1 mm/min	MPa	90 - 100
Flexural modulus	D-790	1 mm/min	MPa	2,200
Rockwell hardness	D-785		R Scale	105 - 115

\*ASTM method except where noted otherwise

## ► Flammability

PALRUF is self-extinguishing and complies with the most demanding international fire resistance standards defined in the field of plastics, as demonstrated in the attached table.

Method	Classification*
DIN 4102	B-1
BS 476=7	Class 1
NSP 92501, 5	M-1
FMRC 4870	Class 1

\*For additional information please contact your PALRAM distributor

## ► Resistance to Weather and UV Radiation

PALRUF retains its physical properties and attractive appearance despite exposure to all types of climatic conditions including harmful UV radiation, humidity, rain and snow. PALRUF provides weather protection over a large temperature range, from - 20 °C to 50 °C. Warning: PALRUF should not be used in the vicinity of chimneys where soot may fall on the sheets.

Inasmuch as PALRAM Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any PALRAM Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. PALRAM Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local PALRAM Industries supplier to ensure that you have obtained the most up to date information.

Europe  
UK  
Israel  
USA  
Australia  
Far East



EUROPE  
PALRAM EUROPE LTD.  
Tel ► (44) 1302 380776  
Fax ► (44) 1302 380788  
sales.europe@palram.com

PALRAM UK  
Tel ► (44) 1302 380738  
Fax ► (44) 1302 380788  
sales.uk@palram.com

ISRAEL  
PALRAM ISRAEL  
Tel ► (972) 4 8459 900  
Fax ► (972) 4 8459 980  
palram@palram.com

USA  
PALRAM AMERICAS  
Tel ► 610 285 9918  
Fax ► 610 285 9928  
palramamericas@palram.com

